

Ultra-dense 1U, 2-way SMP server that helps you do more with less



IBM *@server* xSeries 335



Highlights

- ***Designed to help increase productivity with this high-performance, rack-dense, 2-way server***
- ***Integrated availability features help lower support costs***
- ***Simplify installation and maintenance with easy-to-use manageability features and software tools***

Your challenge is to do more with less—serve more Web pages, handle more secure connections, support more e-mail users—all while reducing cost and saving space. The IBM *@server*™ xSeries® 335 meets the challenge.

Better performance

With dual high-speed Intel® Xeon™ processors, the x335 delivers maximum xSeries performance density in a flexible stand-alone server.

Count on the x335 for robust availability features that help keep servers running. Increase uptime with:

- *Integrated hard disk drive (HDD) mirroring for data protection*
- *Light Path Diagnostics to help identify problem components*

- *Predictive Failure Analysis® on memory, processors, HDDs, fans, VRMs and power supply*

Superior manageability

Powerful tools, including IBM Director, simplify system management—helping you conserve resources.

- *Remote Deployment Manager is designed to help simplify server installation by remotely deploying hundreds of servers from a single location.*
- *IBM Cable Chaining Technology simplifies cabling and helps reduce behind-the-rack clutter.*

The x335 helps deliver the performance business needs to succeed, the manageability to unburden IT staff and reliability to provide peace of mind—all in a small form factor.

Get it now

go to **ibm.com/eserver/xseries** or call 1 888 **ShopIBM**
to buy direct or to locate an IBM reseller.



© Copyright IBM Corporation 2003

Produced in the USA

10-03

All Rights Reserved

IBM reserves the right to change specifications or other product information without notice. This publication could include technical inaccuracies or typographical errors. References herein to IBM products and services do not imply that IBM intends to make them available in other countries. IBM makes no representations or warranties regarding third-party products or services. IBM PROVIDES THIS PUBLICATION "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions; therefore, this disclaimer may not apply to you.

IBM @server systems are assembled in the U.S., Great Britain, Japan, Australia and Brazil and comprise U.S. and non-U.S. components.

IBM, the IBM logo, the e-business logo, Chipkill, @server, Predictive Failure Analysis and xSeries are trademarks of IBM Corporation in the United States and/or other countries.

Intel is a registered trademark and Xeon is a trademark of Intel Corporation. Microsoft, Windows, Windows NT and the Windows logo are trademarks of Microsoft Corporation. Other product, company and service names may be trademarks or service marks of others.

¹ GB = 1,000,000,000 bytes when referring to storage capacity. Accessible capacity is less.

² For a copy of the IBM Statement of Limited Warranty, call 1 800 426-7378. Telephone support may be subject to additional charges. For onsite labor, IBM will attempt to diagnose and resolve the problem remotely before sending a technician.

xSeries 335 at a glance

Form Factor	Rack/1U
Processor	Intel Xeon processor up to 3.2GHz/533MHz front-side bus (NEW)
Number of processors (std/max)	1/2
Cache (max)	Up to 1MB L3
Memory (std/max)	512MB or 1GB/8GB PC2100 ECC DDR Chipkill™
Expansion Slots	2 PCI-X (64-bit 100MHz)
Disk bays (total/hot-swap)	2/2
Maximum internal storage	293.6GB ¹ Ultra320 SCSI or 240GB IDE
Network	Dual integrated 10/100/1000 Ethernet
Power supply (std/max)	332W 1/1 or 411W 1/1
Hot-swap components	Ultra320 SCSI hard disk drives
RAID support	Integrated RAID-1 (mirroring)
Systems management	Automatic Server Restart; Predictive Failure Analysis on hard disk drives, processors, VRMs, fans and memory; Light Path Diagnostics; Integrated System Management Processor; IBM Director, ServerGuide, the optional Remote Supervisor Adapter and optional Remote Deployment Manager
Operating systems supported	Microsoft® Windows® Server 2003, Windows 2000®/Advanced Server, Windows NT, Red Hat Linux, SuSE Linux, Novell NetWare, SCO Open UNIX 8.0 (UnixWare 7.1.2) and SCO OpenServer 5.0.6a
Limited warranty²	3-year onsite limited warranty

For more information:

World Wide Web

U.S.	ibm.com/eserver/xseries
Canada	ibm.com/ca/eserver/xseries

Buy Direct

U.S.	1 888 SHOP IBM
Canada	1 888 SHOP IBM

Reseller locator and generation information

U.S.	1 800 426-4968
Canada	1 800 426-2255